

TABELLA SCELTA UGELLO TESTINA - NOZZLE SELECTION CHART FOR CLEANING HEADS

Fatt.Portata								
SIZE	↓	M4 ( CORTI )	M4 ( CORTI )	M4	1/4 NPT	Con ventolina		With flow straightener
		(0°) INOX AISI303	(0°) INOX AISI316	(0°) INOX AISI303	(5°) Standard	1/8 NPT (0°) Standard	1/4 NPT (0°) Standard	1/4 NPT (0°) Prol-Extended
TAPPO			80.0890.60					
016	3,3 0,9		80.0899.60	25.1189.51				
O2	4,6 1,2	80.0350.51	80.0892.60	25.1190.51		16.1363.20		
O23	5,0 1,3			25.1191.51				
O25	5,6 1,5	80.0351.51	80.0893.60	25.1091.51				
O27	6,1 1,6			25.1192.51				
O3	6,7 1,8	80.0352.51	80.0882.60	25.1092.51	16.1305.30	16.1363.30	16.1380.30	
O32	7,1 1,9			25.1193.51				
O35	7,8 2,1	80.0353.51	80.0883.60	25.1093.51			16.1380.35	
O37	8,4 2,2			25.1098.51				
O4	9,1 2,4	80.0354.51	80.0884.60	25.1094.51	16.1305.40	16.1363.40	16.1380.40	
O43	9,7 2,6			25.1194.51				
O45	10,3 2,7		80.0885.60	25.1095.51		16.1363.45	16.1380.45	
O5	11,2 3,0		80.0895.60	25.1195.51	16.1305.50	16.1363.50	16.1380.50	
O53	12,0 3,2			25.1196.51				
O55	12,6 3,3		80.0886.60	25.1197.51			16.1380.55	
O6	13,7 3,6		80.0887.60	25.1186.51	16.1305.60	16.1363.60	16.1380.60	
O65	14,8 3,9		80.0888.60	25.1198.51			16.1380.65	
O7	16,0 4,2		80.0889.60	25.1199.51	16.1305.70	16.1363.70	16.1380.70	80.0418.23
O8	18,2 4,8		80.0891.60	25.1085.51	16.1305.80			80.0419.23
O9	21,0 5,5					16.1363.90		80.0420.23
O95	22,0 5,8							80.0421.23
11	25,0 6,6							80.0422.23
12	27,0 7,1							80.0423.23
13	30,0 7,9							80.0424.23
14	32,0 8,5							80.0425.23
15	34,0 9,0					16.1363.15		80.0426.23
16	36,0 9,5							80.0427.23
18	41,0 10,8							80.0428.23
19	43,0 11,4							80.0429.23
20	46,0 12,2							80.0430.23
25	57,0 15,1							80.0435.23
30	68,0 18,0							80.0440.23
40	91,0 24,0							80.0444.23
50	114,0 30,1							80.0445.23